

MajorFC2000 - 2000 VA Frequency Converter

The **MajorFC2000** is a compact, highly reliable, telecom quality, AC to AC Frequency Converter.

The **MajorFC2000** features full electronic protection, high efficiency and low output noise. The built-in fan provides sufficient airflow for operation without de-rating up to 50°C ambient temperature. Extended temperature (-40 to +65°C), ruggedization and conformal coating are available.

**Product Features**

- Autoranging Input: 60/50/400 Hz
- 60, 50 or 400 Hz Output Available
- Custom Input and Output Voltages available
- Compact size, light weight
- Pure sine wave output (60, 50 or 400 Hz)
- Full electronic protection
- Telecom quality
- Rugged Enclosed Case standard
- Options:
 - ▶ Dry contact failure alarm
 - ▶ Ruggedization
 - ▶ Conformal Coating
 - ▶ Extended Temp. (-40 to +65°C)

Product Specifications

Input Voltage:	115 or 230VAC, $\pm 20\%$, 48-410 Hz Standard. Other inputs available.
Input Protection	Thermal fuse, Inrush current limiting and Reverse polarity protection
Input Isolation	Input-chassis / Input-output / Output-chassis: 2250VDC
Output Voltage	115VAC/60Hz @ 17.3A Standard. (230VAC/50Hz @ 8.6A and 115VAC/400Hz @ 17.3A Available.) Continuous output with grounded neutral. Isolated floating output available.
Efficiency	Min 78% at full load
Line Regulation	Maximum 0.5%
Load Regulation	Maximum $\pm 6\%$ from 10% load to full load
Output Protection	Current limiting with short circuit protection. Thermal shutdown with automatic reset in case of insufficient airflow
RFI Suppression	Meets requirements of EN 55022: 1987 Class B conducted emissions
Crest Factor	Maximum 3.0 at 90% load
Harmonics (THD)	Less than 5% at full load
Operating Temp.	0°C to +50°C (internal fan)
Temp. Drift	0.05% per°C over operating temperature range
Dimensions	5.3"H x 16.75"W x 13.8"L (Enclosed Case)
Connections	Input: Compression-type terminal. Output: Standard AC Receptical
Weight	25 pounds (11.35Kg)
Warranty	Twelve months subject to client application within accepted engineering practice. Designed to meet common approval requirements.

Specifications subject to change